



Frank O'Bannon
Governor

Lori F. Kaplan
Commissioner

100 North Senate Avenue
P. O. Box 6015
Indianapolis, Indiana 46206-6015
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

MINOR SOURCE OPERATING PERMIT OFFICE OF AIR QUALITY

**LAU Industries, Inc.
843 Indianapolis Avenue
Lebanon, Indiana 46052**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the emission units described in Section A (Source Summary) of this permit.

This permit is issued to the above mentioned company under the provisions of 326 IAC 2-1.1, 326 IAC 2-6.1 and 40 CFR 52.780, with conditions listed on the attached pages.

Operation Permit No.: MSOP 011-14721-00039	
Issued by: Paul Dubenetzky, Branch Chief Office of Air Quality	Issuance Date: January 21, 2003 Expiration Date: January 21, 2008

First Minor Permit Revision 011-16931-00039	Condition Affected: A.2 Section Affected: D.1
Issued by: Paul Dubenetzky, Branch Chief Office of Air Quality	Issuance Date:

TABLE OF CONTENTS

A	SOURCE SUMMARY	4
A.1	General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]	
A.2	Emissions Units and Pollution Control Equipment Summary	
B	GENERAL CONDITIONS	6
B.1	Permit No Defense [IC 13]	
B.2	Definitions	
B.3	Effective Date of the Permit [IC 13-15-5-3]	
B.4	Permit Term and Renewal [326 IAC 2-6.1-7(a)][326 IAC 2-1.1-9.5]	
B.5	Modification to Permit [326 IAC 2]	
B.6	Annual Notification [326 IAC 2-6.1-5(a)(5)]	
B.7	Preventive Maintenance Plan [326 IAC 1-6-3]	
B.8	Permit Revision [326 IAC 2-5.1-3(e)(3)] [326 IAC 2-6.1-6]	
B.9	Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)] [326 IAC 2-6.1-5(a)(4)]	
B.10	Transfer of Ownership or Operation [326 IAC 2-6.1-6(d)(3)]	
B.11	Annual Fee Payment [326 IAC 2-1.1-7]	
C	SOURCE OPERATION CONDITIONS	7
C.1	Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [40 CFR 52 Subpart P][326 IAC 6-3-2]	
C.2	Permit Revocation [326 IAC 2-1-9]	
C.3	Opacity [326 IAC 5-1]	
C.4	Fugitive Dust Emissions [326 IAC 6-4]	
C.5	Stack Height [326 IAC 1-7]	
C.6	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]	
	Testing Requirements	
C.7	Performance Testing [326 IAC 3-6] [326 IAC 2-1.1-11]	
	Compliance Requirements [326 IAC 2-1.1-11]	
C.8	Compliance Requirements [326 IAC 2-1.1-11]	
	Compliance Monitoring Requirements	
C.9	Compliance Monitoring [326 IAC 2-1.1-11]	
C.10	Monitoring Methods [326 IAC 3]	
C.11	Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 1-6]	
C.12	Actions Related to Noncompliance Demonstrated by a Stack Test	
	Record Keeping and Reporting Requirements	
C.13	Malfunctions Report [326 IAC 1-6-2]	
C.14	General Record Keeping Requirements [326 IAC 2-6.1-2]	
C.15	General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]	
D.1	EMISSIONS UNIT OPERATION CONDITIONS:	15
	Emission Limitations and Standards [326 IAC 2-6.1-5(1)]	
D.1.1	Volatile Organic Compounds [326 IAC 8-2-9]	
D.1.2	Volatile Organic Compounds [326 IAC 8-2-9]	
D.1.3	Particulate Matter (PM) [326 IAC 6-3-2(c)]	
D.1.4	Particulate Matter (PM) [326 IAC 6-3-2(d)]	
D.1.5	Preventive Maintenance Plan [326 IAC 1-6-3]	

Compliance Determination Requirements [326 IAC 2-1.1-11]

D.1.6 Volatile Organic Compounds (VOC)

Compliance Monitoring Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.7 Paint Spray Booth Monitoring

Record Keeping and Reporting Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.8 Record Keeping Requirements

Malfunction Report	18
Annual Notification	20

SECTION A

SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in Conditions A.1 and A.2 are descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]

The Permittee owns and operates a stationary fan manufacturing source.

Authorized Individual:	Plant Manager
Source Address:	843 Indianapolis Avenue, Lebanon, Indiana 46052
Mailing Address:	P.O. Box 646, Lebanon, Indiana 46052
General Source Phone:	765-482-3650
SIC Code:	3564
County Location:	Boone
Source Location Status:	Attainment for all criteria pollutants
Source Status:	Minor Source Operating Permit Minor Source, under PSD Rules; Minor Source, Section 112 of the Clean Air Act

A.2 Emissions Units and Pollution Control Equipment Summary

This stationary source is approved to operate the following emissions units and pollution control devices:

- (a) One (1) paint spray booth, known as Booth 1, equipped with air atomization and HVLP spray applicators, and dry filters for PM overspray control, installed in 1964, reconstructed in 2002, exhausted through stack P/1, capacity: 42 fan parts per hour.
- (b) One (1) paint spray booth, known as Booth 2, equipped with air atomization and HVLP spray applicators, and dry filters for PM overspray control, installed in 1974, reconstructed in 2002, exhausted through stack P/2, capacity: 21 fan parts per hour.
- (c) One (1) paint spray booth, known as Booth 3, equipped with air atomization and HVLP spray applicators, and dry filters for PM overspray control, installed in 1984, reconstructed in 2002, exhausted through stack P/3, capacity: 4 compressor units per hour.
- (d) One (1) laser cutting machine, equipped with a Torit dust collector for particulate control, installed in 2002, exhausted inside the building, capacity: 453 inches of metal per minute.
- (e) Two (2) natural gas-fired air make-up units, identified as MUA-1 and MUA-2, installed in May 2002, rated at: 4.00 million British thermal units per hour, each.
- (f) Twelve (12) Metal Inert Gas (MIG) welding stations, capacity: 7.00 pounds of wire per hour, each.
- (g) Fourteen (14) Metal Inert Gas (MIG) welding stations, installed in 2003, capacity: 7.00 pounds of wire per hour, each, and a process weight rate of 50 pounds per hour, each.
- (h) Three (3) Stick welding stations, capacity: 1.80 pounds of wire per hour, each.

- (i) Three (3) Tungsten Inert Gas (TIG) welding stations, capacity: 2.00 pounds of wire per hour, each.
- (j) One (1) plasma flame cutting station, equipped with a torit dust collector for particulate matter (PM) control, exhausted inside the building, capacity: 180 inches of metal per minute.
- (k) One (1) radial arm saw, equipped with a fabric dust collector for particulate matter (PM) control, installed in 1964, exhausted inside the building, capacity: 70.6 pounds of wood per hour.

SECTION B

GENERAL CONDITIONS

THIS SECTION OF THE PERMIT IS BEING ISSUED UNDER THE PROVISIONS OF 326 IAC 2-1.1 AND 40 CFR 52.780, WITH CONDITIONS LISTED BELOW.

B.1 Permit No Defense [IC 13]

This permit to operate does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

B.2 Definitions

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations IC 13-11, 326 IAC 1-2, and 326 IAC 2-1.1-1 shall prevail.

B.3 Effective Date of the Permit [IC13-15-5-3]

Pursuant to IC 13-15-5-3, this permit becomes effective upon its issuance.

B.4 Permit Term and Renewal [326 IAC 2-6.1-7(a)][326 IAC 2-1.1-9.5]

This permit is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions of this permit do not affect the expiration date.

The Permittee shall apply for an operation permit renewal at least ninety (90) days prior to the expiration date. If a timely and sufficient permit application for a renewal has been made, this permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied.

B.5 Modification to Permit [326 IAC 2]

All requirements and conditions of this operating permit shall remain in effect unless modified in a manner consistent with procedures established for modifications of operating permits pursuant to 326 IAC 2 (Permit Review Rules).

B.6 Annual Notification [326 IAC 2-6.1-5(a)(5)]

- (a) Annual notification shall be submitted to the Office of Air Quality stating whether or not the source is in operation and in compliance with the terms and conditions contained in this permit.
- (b) Noncompliance with any condition must be specifically identified. If there are any permit conditions or requirements for which the source is not in compliance at any time during the year, the Permittee must provide a narrative description of how the source did or will achieve compliance and the date compliance was, or will be, achieved. The notification must be signed by an authorized individual.
- (c) The annual notice shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in the format attached no later than March 1 of each year to:

Compliance Branch, Office of Air Quality
Indiana Department of Environmental Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, IN 46206-6015

- (d) The notification shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

B.7 Preventive Maintenance Plan [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall maintain and implement Preventive Maintenance Plans (PMPs) including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) The Permittee shall implement the PMPs as necessary to ensure that failure to implement a PMP does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or contributes to any violation. The PMP does not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (d) Records of preventive maintenance shall be retained for a period of at least five (5) years. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

B.8 Permit Revision [326 IAC 2-5.1-3(e)(3)] [326 IAC 2-6.1-6]

- (a) Permit revisions are governed by the requirements of 326 IAC 2-6.1-6.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

Any such application shall be certified by an "authorized individual" as defined by 326 IAC 2-1.1-1.
- (c) The Permittee shall notify the OAQ within thirty (30) calendar days of implementing a notice-only change. [326 IAC 2-6.1-6(d)]

B.9 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)] [326 IAC 2-6.1-5(a)(4)]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.10 Transfer of Ownership or Operation [326 IAC 2-6.1-6(d)(3)]

Pursuant to 326 IAC 2-6.1-6(d)(3):

- (a) In the event that ownership of this source is changed, the Permittee shall notify IDEM, OAQ, Permits Branch, within thirty (30) days of the change.
- (b) The written notification shall be sufficient to transfer the permit to the new owner by a notice-only change pursuant to 326 IAC 2-6.1-6(d)(3).
- (c) IDEM, OAQ, shall issue a revised permit.

The notification which shall be submitted by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1.

B.11 Annual Fee Payment [326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing.
- (b) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, I/M & Billing Section), to determine the appropriate permit fee.

SECTION C

SOURCE OPERATION CONDITIONS

Entire Source

C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [40 CFR 52 Subpart P][326 IAC 6-3-2]

- (a) Pursuant to 40 CFR 52 Subpart P, the allowable particulate matter emissions rate from any process not already regulated by 326 IAC 6-1 or any New Source Performance Standard, and which has a maximum process weight rate less than 100 pounds per hour shall not exceed 0.551 pounds per hour.
- (b) Pursuant to 326 IAC 6-3-2(e)(2), the allowable particulate emissions rate from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.2 Permit Revocation [326 IAC 2-1.1-9]

Pursuant to 326 IAC 2-1-9(a)(Revocation of Permits), this permit to operate may be revoked for any of the following causes:

- (a) Violation of any conditions of this permit.
- (b) Failure to disclose all the relevant facts, or misrepresentation in obtaining this permit.
- (c) Changes in regulatory requirements that mandate either a temporary or permanent reduction of discharge of contaminants. However, the amendment of appropriate sections of this permit shall not require revocation of this permit.
- (d) Noncompliance with orders issued pursuant to 326 IAC 1-5 (Episode Alert Levels) to reduce emissions during an air pollution episode.
- (e) For any cause which establishes in the judgment of IDEM, the fact that continuance of this permit is not consistent with purposes of this article.

C.3 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor in a six (6) hour period.

C.4 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

C.5 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted by using good engineering practices (GEP) pursuant to 326 IAC 1-7-3.

C.6 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by an "authorized individual" as defined by 326 IAC 2-1.1-1.

- (e) Procedures for Asbestos Emission Control
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.

- (f) Indiana Accredited Asbestos Inspector
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement that the inspector be accredited, pursuant to the provisions of 40 CFR 61, Subpart M, is federally enforceable.

Testing Requirements

C.7 Performance Testing [326 IAC 3-6] [326 IAC 2-1.1-11]

- (a) Compliance testing on new emissions units shall be conducted within 60 days after achieving maximum production rate, but no later than 180 days after initial start-up, if specified in Section D of this approval. All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date.

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date.
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by the IDEM, OAQ, if the source submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.8 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U.S. EPA.

Compliance Monitoring Requirements

C.9 Compliance Monitoring [326 IAC 2-1.1-11]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. All monitoring and record keeping requirements not already legally required shall be implemented when operation begins.

C.10 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60, Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

C.11 Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 1-6]

- (a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. A CRP shall be submitted to IDEM, OAQ upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and comprised of:
- (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected timeframe for taking reasonable response steps.
 - (2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan and the Permittee documents such response in accordance with subsection (e) below, the Permittee shall amend its Compliance Response Plan to include such response steps taken.
- (b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:
- (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan; or
 - (2) If none of the reasonable response steps listed in the Compliance Response Plan is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.
 - (3) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, the IDEM, OAQ shall be promptly notified of the expected date of the shut down, the status of the applicable compliance monitoring parameter with respect to normal, and the results of the actions taken up to the time of notification.
 - (4) Failure to take reasonable response steps shall constitute a violation of the permit.
- (c) The Permittee is not required to take any further response steps for any of the following reasons:
- (1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied.
 - (3) An automatic measurement was taken when the process was not operating.

- (4) The process has already returned or is returning to operating within “normal” parameters and no response steps are required.
- (d) When implementing reasonable steps in response to a compliance monitoring condition, if the Permittee determines that an exceedance of an emission limitation has occurred, the Permittee shall report such deviations pursuant to Section B-Deviations from Permit Requirements and Conditions.
- (e) The Permittee shall record all instances when response steps are taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.
- (f) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.

C.12 Actions Related to Noncompliance Demonstrated by a Stack Test

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected emissions unit while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The documents submitted pursuant to this condition do not require the certification by an “authorized individual” as defined by 326 IAC 2-1.1-1.

Record Keeping and Reporting Requirements

C.13 Malfunctions Report [326 IAC 1-6-2]

Pursuant to 326 IAC 1-6-2 (Records; Notice of Malfunction):

- (a) A record of all malfunctions, including startups or shutdowns of any facility or emission control equipment, which result in violations of applicable air pollution control regulations or applicable emission limitations shall be kept and retained for a period of three (3) years and shall be made available to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) or appointed representative upon request.
- (b) When a malfunction of any facility or emission control equipment occurs which lasts more than one (1) hour, said condition shall be reported to OAQ, using the Malfunction Report Forms (2 pages). Notification shall be made by telephone or facsimile, as soon as practicable, but in no event later than four (4) daytime business hours after the beginning of said occurrence.

- (c) Failure to report a malfunction of any emission control equipment shall constitute a violation of 326 IAC 1-6, and any other applicable rules. Information of the scope and expected duration of the malfunction shall be provided, including the items specified in 326 IAC 1-6-2(a) (1) through (6).
- (d) Malfunction is defined as any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner. [326 IAC 1-2-39]

C.14 General Record Keeping Requirements [326 IAC 2-6.1-5]

- (a) Records of all required data, reports and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, a record keeping requirements not already legally required shall be implemented when operation begins.

C.15 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]

- (a) Reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015
- (b) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) Unless otherwise specified in this permit, any report required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. The reports do not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (d) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period. Reporting periods are based on calendar years.

SECTION D.1

EMISSIONS UNIT OPERATION CONDITIONS

Emissions Unit Description:

- (a) One (1) paint spray booth, known as Booth 1, equipped with air atomization and HVLP spray applicators, and dry filters for PM overspray control, installed in 1964, reconstructed in 2002, exhausted through stack P/1, capacity: 42 fan parts per hour.
- (b) One (1) paint spray booth, known as Booth 2, equipped with air atomization and HVLP spray applicators, and dry filters for PM overspray control, installed in 1974, reconstructed in 2002, exhausted through stack P/2, capacity: 21 fan parts per hour.
- (c) One (1) paint spray booth, known as Booth 3, equipped with air atomization and HVLP spray applicators, and dry filters for PM overspray control, installed in 1984, reconstructed in 2002, exhausted through stack P/3, capacity: 4 compressor units per hour.
- (d) One (1) laser cutting machine, equipped with a Torit dust collector for particulate control, installed in 2002, exhausted inside the building, capacity: 453 inches of metal per minute.
- (e) Two (2) natural gas-fired air make-up units, identified as MUA-1 and MUA-2, installed in May 2002, rated at: 4.00 million British thermal units per hour, each.
- (f) Twenty-six (26) Metal Inert Gas (MIG) welding stations, capacity: 7.00 pounds of wire per hour, each.
- (g) Fourteen (14) Metal Inert Gas (MIG) welding stations, installed in 2003, capacity: 7.00 pounds of wire per hour, each, and a process weight rate of 50 pounds per hour, each.
- (h) Three (3) Stick welding stations, capacity: 1.80 pounds of wire per hour, each.
- (i) Three (3) Tungsten Inert Gas (TIG) welding stations, capacity: 2.00 pounds of wire per hour, each.
- (j) One (1) plasma flame cutting station, equipped with a torit dust collector for particulate matter (PM) control, exhausted inside the building, capacity: 180 inches of metal per minute.
- (k) One (1) radial arm saw, equipped with a fabric dust collector for particulate matter (PM) control, installed in 1964, exhausted inside the building, capacity: 70.6 pounds of wood per hour.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-6.1-5(1)]

D.1.1 Volatile Organic Compounds [326 IAC 8-2-9]

- (a) Pursuant to 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations), the daily volume weighted average volatile organic compound (VOC) content of coating applied to the metal fan parts in Booth 1 and Booth 2 shall be limited to 3.5 pounds of VOCs per gallon of coating less water, as delivered to the applicator for any calendar day, for forced warm air dried coatings.
- (b) Pursuant to 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations), solvent sprayed from the application equipment during clean up or color changes shall be directed into containers. Such containers shall be closed as soon as such solvent spraying is complete, and the waste

solvent shall be disposed of in such a manner that evaporation is minimized.

D.1.2 Volatile Organic Compounds [326 IAC 8-2-9]

The potential to emit of VOC from the one (1) paint spray booth, identified as Booth 3, is less than fifteen (15) pounds per day, therefore, 326 IAC 8-2-9 does not apply. Any change or modification which would increase the potential to emit VOC to fifteen (15) pounds per day or more from this paint spray booth shall obtain prior approval from IDEM, OAQ.

D.1.3 Particulate Matter (PM) [326 IAC 6-3-2(c)]

Pursuant to 326 IAC 6-3-2 (Particulate emission limitations, work practices, and control technologies), and 40 CFR 52 Subpart P, the allowable PM emission rate from the twelve (12) Metal Inert Gas (MIG) welding stations, the three (3) stick welding stations, and the three (3) Tungsten Inert Gas (TIG) welding stations shall not exceed 6.52 pounds of PM per hour at a process weight rate of 4,000 pounds per hour, each.

The pounds per hour limitation was calculated with the following equation:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

D.1.4 Particulate Matter (PM) [326 IAC 6-3-2(d)]

The surface coating operation shall be controlled by a dry particulate filter, and the Permittee shall operate the control device in accordance with manufacturer's specifications.

D.1.5 Preventive Maintenance Plan [326 IAC 1-6-3]

A Preventive Maintenance Plan, in accordance with Section C - Preventive Maintenance Plan, of this permit, is required for the three (3) paint spray booths, the one (1) coal slag shotblaster, the two (2) plasma flame cutting stations, and the one (1) radial arm saw and their control devices.

Compliance Determination Requirements [326 IAC 2-1.1-11]

D.1.6 Volatile Organic Compounds (VOC)

Compliance with the VOC content and usage limitations contained in Condition D.1.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3)(A) using formulation data supplied by the coating manufacturer and the daily volume weighted average of VOC content. This shall be calculated using the following formula, where n is the number of coatings (c):

$$c = n$$

$$\frac{3 \text{ production rate (units/day)} \times \text{coating (gallons/unit)} \times \text{VOC content (pounds/gallons of coating less water)}}{c = 1}$$

$$c = n$$

$$3 \text{ production rate (units/day)} \times \text{coating (gallons/unit)}$$

$$c = 1$$

However, IDEM, OAQ reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Compliance Monitoring Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.7 Paint Spray Booth Monitoring

(a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made

of the overspray from the surface coating booth stacks P/1, P/2, and P/3 while one (1) or more of the booths are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

- (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Record Keeping and Reporting Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.8 Record Keeping Requirements

- (a) To document compliance with Condition D.1.1, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken daily and shall be complete and sufficient to establish compliance with the VOC content limit established in Condition D.1.1.
 - (1) The amount and VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (2) The total VOC usage for each day; and
 - (3) The volume weighted VOC content of the coatings used for each day.
- (b) To document compliance with Condition D.1.2, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC usage limit established in Condition D.1.2.
 - (1) The amount and VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (2) The total VOC usage for each month; and
 - (3) The weight of VOCs emitted for each compliance period.
- (c) To document compliance with Condition D.1.7, the Permittee shall maintain records of the results of the inspections required under Condition and D.1.7.
- (d) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

MALFUNCTION REPORT

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
FAX NUMBER - 317 233-5967**

**This form should only be used to report malfunctions applicable to Rule 326 IAC 1-6
and to qualify for the exemption under 326 IAC 1-6-4.**

THIS FACILITY MEETS THE APPLICABILITY REQUIREMENTS BECAUSE IT HAS POTENTIAL TO EMIT 25 TONS/YEAR PARTICULATE MATTER ?_____, 25 TONS/YEAR SULFUR DIOXIDE ?_____, 25 TONS/YEAR NITROGEN OXIDES ?_____, 25 TONS/YEAR VOC ?_____, 25 TONS/YEAR HYDROGEN SULFIDE ?_____, 25 TONS/YEAR TOTAL REDUCED SULFUR ?_____, 25 TONS/YEAR REDUCED SULFUR COMPOUNDS ?_____, 25 TONS/YEAR FLUORIDES ?_____, 100 TONS/YEAR CARBON MONOXIDE ?_____, 10 TONS/YEAR ANY SINGLE HAZARDOUS AIR POLLUTANT ?_____, 25 TONS/YEAR ANY COMBINATION HAZARDOUS AIR POLLUTANT ?_____, 1 TON/YEAR LEAD OR LEAD COMPOUNDS MEASURED AS ELEMENTAL LEAD ?_____, OR IS A SOURCE LISTED UNDER 326 IAC 2-5.1-3(2) ?_____. EMISSIONS FROM MALFUNCTIONING CONTROL EQUIPMENT OR PROCESS EQUIPMENT CAUSED EMISSIONS IN EXCESS OF APPLICABLE LIMITATION _____.

THIS MALFUNCTION RESULTED IN A VIOLATION OF: 326 IAC _____ OR, PERMIT CONDITION # _____ AND/OR PERMIT LIMIT OF _____

THIS INCIDENT MEETS THE DEFINITION OF 'MALFUNCTION' AS LISTED ON REVERSE SIDE ? Y N

THIS MALFUNCTION IS OR WILL BE LONGER THAN THE ONE (1) HOUR REPORTING REQUIREMENT ? Y N

COMPANY: _____ PHONE NO. : _____
LOCATION: (CITY AND COUNTY) _____
PERMIT NO. _____ AFS PLANT ID: _____ AFS POINT ID: _____ INSP: _____
CONTROL/PROCESS DEVICE WHICH MALFUNCTIONED AND REASON: _____

DATE/TIME MALFUNCTION STARTED: ____/____/20____ _____ AM / PM

ESTIMATED HOURS OF OPERATION WITH MALFUNCTION CONDITION: _____

DATE/TIME CONTROL EQUIPMENT BACK-IN SERVICE ____/____/20____ _____ AM / PM

TYPE OF POLLUTANTS EMITTED: TSP, PM-10, SO₂, VOC, OTHER: _____

ESTIMATED AMOUNT OF POLLUTANT EMITTED DURING MALFUNCTION: _____

MEASURES TAKEN TO MINIMIZE EMISSIONS: _____

REASONS WHY FACILITY CANNOT BE SHUTDOWN DURING REPAIRS:

CONTINUED OPERATION REQUIRED TO PROVIDE ESSENTIAL* SERVICES: _____
CONTINUED OPERATION NECESSARY TO PREVENT INJURY TO PERSONS: _____
CONTINUED OPERATION NECESSARY TO PREVENT SEVERE DAMAGE TO EQUIPMENT: _____
INTERIM CONTROL MEASURES: (IF APPLICABLE) _____

MALFUNCTION REPORTED BY: _____ TITLE: _____
(SIGNATURE IF FAXED)

MALFUNCTION RECORDED BY: _____ DATE: _____ TIME: _____

**Please note - This form should only be used to report malfunctions
applicable to Rule 326 IAC 1-6 and to qualify for
the exemption under 326 IAC 1-6-4.**

326 IAC 1-6-1 Applicability of rule

Sec. 1. This rule applies to the owner or operator of any facility required to obtain a permit under 326 IAC 2-5.1 or 326 IAC 2-6.1.

326 IAC 1-2-39 "Malfunction" definition

Sec. 39. Any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner.

* **Essential services** are interpreted to mean those operations, such as, the providing of electricity by power plants. Continued operation solely for the economic benefit of the owner or operator shall not be sufficient reason why a facility cannot be shutdown during a control equipment shutdown.

If this item is checked on the front, please explain rationale:

Indiana Department of Environmental Management Office of Air Quality

Technical Support Document (TSD) for a Minor Permit Revision to a Minor Source Operating Permit

Source Background and Description

Source Name:	LAU Industries, Inc.
Source Location:	843 Indianapolis Avenue, Lebanon, Indiana 46052
County:	Boone
SIC Code:	3564
Operation Permit No.:	MSOP 011-14721-00039
Operation Permit Issuance Date:	January 21, 2003
Minor Permit Revision No.:	MPR 011-16931-00039
Permit Reviewer:	Craig J. Friederich

The Office of Air Quality (OAQ) has reviewed a revision application from LAU Industries, Inc. relating to the construction and operation of the following emission units and pollution control devices:

Fourteen (14) Metal Inert Gas (MIG) welding stations, installed in 2003, capacity: 7.00 pounds of wire per hour, each, and a process weight rate of 50 pounds per hour, each.

History

On January 7, 1998, LAU Industries, Inc. submitted an application to the OAQ requesting to add additional Metal Inert Gas (MIG) welding stations to their existing plant. LAU Industries, Inc. was issued a Minor Source Operating Permit (MSOP) on January 21, 2003

Enforcement Issue

There are no enforcement actions pending.

Recommendation

The staff recommends to the Commissioner that the MSOP Minor Permit Revision be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An application for the purposes of this review was received on December 18, 2002.

Emission Calculations

See page 1 of 1 TSD Appendix A of this document for detailed emissions calculations.

Potential To Emit of Revision

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as "the maximum capacity of a stationary source to emit any air pollutant under its physical and operational design. Any physical or opera-

tional limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U.S. EPA.”

This table reflects the PTE before controls for this revision. Control equipment is not considered federally enforceable until it has been required in a federally enforceable permit.

Pollutant	Potential To Emit (tons/year)
PM	10.3
PM ₁₀	10.3
SO ₂	--
VOC	--
CO	--
NO _x	--

HAPs	Potential To Emit (tons/year)
Total HAPs	0.019

Justification for Revision

This revision is being performed pursuant to 326 IAC 2-6.1-6(g)(4)(B), “Modifications that would have the potential to emit less than twenty-five (25) tons per year and greater than five (5) tons per year of Particulate matter (PM) or particulate matter less than ten (10) microns (PM₁₀).”

County Attainment Status

The source is located in Boone County.

Pollutant	Status
PM ₁₀	attainment
SO ₂	attainment
NO ₂	attainment
Ozone	attainment
CO	attainment
Lead	attainment

- (a) Volatile organic compounds (VOC) are precursors for the formation of ozone. Therefore, VOC emissions are considered when evaluating the rule applicability relating to the ozone standards. Boone County has been designated as attainment or unclassifiable for ozone. Therefore, VOC emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.

- (b) Boone County has been classified as attainment or unclassifiable for all remaining criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.
- (c) Fugitive Emissions
Since this type of operation is not one of the 28 listed source categories under 326 IAC 2-2 and since there are no applicable New Source Performance Standards that were in effect on August 7, 1980, the fugitive PM emissions are not counted toward determination of PSD and Emission Offset applicability.

Source Status

Existing Source PSD or Emission Offset Definition (emissions after controls, based upon 8760 hours of operation per year at rated capacity and/or as otherwise limited):

Pollutant	Emissions (tons/year)
PM	22.7
PM ₁₀	22.8
SO ₂	0.021
VOC	9.75
CO	2.94
NO _x	3.50

- (a) This existing source is not a major stationary source because no attainment regulated pollutant is emitted at a rate of two-hundred fifty (250) tons per year or more, and it is not one of the 28 listed source categories.
- (b) These emissions are based upon the TSD for MSOP 011-14721-00039

Potential to Emit of Revision After Issuance

The table below summarizes the potential to emit, reflecting all limits, of the significant emission units.

	Potential to Emit (tons/year)						
Process/facility	PM	PM ₁₀	SO ₂	VOC	CO	NO _x	HAPs
Proposed Revision	10.3	10.3	--	--	--	--	0.019
Existing Emission Units	22.7	22.8	0.021	9.75	2.94	3.50	14.3
Total	33.0	33.1	0.021	9.75	2.94	3.50	14.3
MSOP Threshold Level	100	100	100	100	100	100	10/25

This revision to the existing MSOP will not change the status of the stationary source because the potential emissions from the entire source will still be less than the Part 70 major source thresholds.

Federal Rule Applicability

- (a) There are no New Source Performance Standards (NSPS) (326 IAC 12 and 40 CFR Part 60) applicable to this proposed revision.
- (b) There are still no National Emission Standards for Hazardous Air Pollutants (NESHAPs) (326 IAC 14, 326 IAC 20, 40 CFR 61 and 40 CFR Part 63) applicable to this proposed revision.

State Rule Applicability - Individual Facilities

326 IAC 2-2 (Prevention of Significant Deterioration (PSD))

The potential to emit of all criteria pollutants is less than two-hundred fifty (250) tons per year, and this source is not one of the 28 listed source categories. Therefore, the requirements of 326 IAC 2-2 are not applicable.

326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)

The particulate from the fourteen (14) Metal Inert Gas (MIG) welding stations shall be limited to 0.551 pounds of PM per hour, each, at a process weight rate of less than 100 pounds per hour, each.

The potential PM emission rate, after controls, is:

$$0.738 \text{ ton/yr} \times (2000 \text{ lbs/ton} / 8760 \text{ hrs/yr}) = 0.168 \text{ lb/hr, each.}$$

The PM emissions from each of the fourteen (14) Metal Inert Gas (MIG) are 0.168 pounds of PM per hour, which is less than the allowable of 0.551 pounds of PM per hour. Therefore, the fourteen (14) Metal Inert Gas (MIG) are in compliance with this rule.

Compliance Requirements

Permits issued under 326 IAC 2-6.1 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-6.1. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

There are no specific Compliance Monitoring requirements for the new welding units.

Proposed Changes

The permit language is changed to read as follows (deleted language appears as ~~strikeouts~~, new language appears in bold):

A.2 Emissions Units and Pollution Control Equipment Summary

- (g) Fourteen (14) Metal Inert Gas (MIG) welding stations, installed in 2003, capacity: 7.00 pounds of wire per hour, each, and a process weight rate of 50 pounds per hour, each.**
- ~~(g h)~~ Three (3) Stick welding stations, capacity: 1.80 pounds of wire per hour, each.
- ~~(h i)~~ Three (3) Tungsten Inert Gas (TIG) welding stations, capacity: 2.00 pounds of wire per hour, each.
- ~~(i j)~~ One (1) plasma flame cutting station, equipped with a torit dust collector for particulate matter (PM) control, exhausted inside the building, capacity: 180 inches of metal per minute.
- ~~(j k)~~ One (1) radial arm saw, equipped with a fabric dust collector for particulate matter (PM) control, installed in 1964, exhausted inside the building, capacity: 70.6 pounds of wood per hour.

SECTION D.1

EMISSIONS UNIT OPERATION CONDITIONS

Emissions Unit Description:

- (g) Fourteen (14) Metal Inert Gas (MIG) welding stations, installed in 2003, capacity: 7.00 pounds of wire per hour, each, and a process weight rate of 50 pounds per hour, each.**
- ~~(g h)~~ Three (3) Stick welding stations, capacity: 1.80 pounds of wire per hour, each.
- ~~(h i)~~ Three (3) Tungsten Inert Gas (TIG) welding stations, capacity: 2.00 pounds of wire per hour, each.
- ~~(i j)~~ One (1) plasma flame cutting station, equipped with a torit dust collector for particulate matter (PM) control, exhausted inside the building, capacity: 180 inches of metal per minute.
- ~~(j k)~~ One (1) radial arm saw, equipped with a fabric dust collector for particulate matter (PM) control, installed in 1964, exhausted inside the building, capacity: 70.6 pounds of wood per hour.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

Conclusion

The construction of this proposed revision shall be subject to the conditions of the attached proposed MSOP Minor Permit Revision No. 011-16931-00039.

Appendix A: Welding Operations

Page 1 of 1 TSD App A

Company Name: LAU Industries, Inc.
Address City IN Zip: 843 Indianapolis Avenue, Lebanon, IN 46502
MSOP REV: 011-16931-00039
Reviewer: Craig J. Friederich
Date: December 18, 2002

PROCESS	Number of Stations	Max. electrode consumption per station (lbs/hr)		EMISSION FACTORS * (lb pollutant / lb electrode)				EMISSIONS (lb/hr)				TOTAL HAPS (lb/hr)
				PM = PM10	Mn	Ni	Cr	PM = PM10	Mn	Ni	Cr	
WELDING												
Submerged Arc	0	0		0.036				0.000	0	0.000	0	0.000
Metal Inert Gas (MIG)(ER5154)	14	7		0.0241	0.00003		0.00001	2.362	0.003332	0.000	0.00098	0.004
Stick (E7018 electrode)	0	0		0.0211				0.000	0	0.000	0	0.000
Tungsten Inert Gas (TIG)(carbon steel)	0	0		0.0055				0.000	0	0.000	0	0.000
Oxyacetylene(carbon steel)	0	0		0.0055				0.000	0	0.000	0	0.000
FLAME CUTTING	Number of Stations	Max. Metal Thickness Cut (in.)	Max. Metal Cutting Rate (in./minute)	EMISSION FACTORS (lb pollutant/1,000 inches cut, 1" thick)				EMISSIONS (lbs/hr)				TOTAL HAPS (lb/hr)
				PM = PM10	Mn	Ni	Cr	PM = PM10	Mn	Ni	Cr	
Oxyacetylene	0	0	0	0.1622	0.0005	0.0001	0.0003	0.000	0.000	0.000	0.000	0.000
Oxymethane	0	0	0	0.0815	0.0002		0.0002	0.000	0.000	0.000	0.000	0.000
Plasma	0	0	0					0.000	0.000	0.000	0.000	0.000
EMISSION TOTALS								PM = PM10	Mn	Ni	Cr	Total HAPs
Potential Emissions lbs/hr								2.36	0.00	0.00	0.00	0.00
Potential Emissions lbs/day								56.68	0.08	0.00	0.02	0.10
Potential Emissions tons/year								10.34	0.015	0.00	0.00	0.019

METHODOLOGY

*Emission Factors are default values for carbon steel unless a specific electrode type is noted in the Process column. Consult AP-42 or other reference for different electrode types.

Welding emissions, lb/hr: (# of stations)(max. lbs of electrode used/hr/station)(emission factor, lb. pollutant/lb. of electrode used)

Cutting emissions, lb/hr: (# of stations)(max. metal thickness, in.)(max. cutting rate, in./min.)(60 min./hr.)(emission factor, lb. pollutant/1,000 in. cut, 1" thick)

Emissions, lbs/day = emissions, lbs/hr x 24 hrs/day

Emissions, tons/yr = emissions, lb/hr x 8,760 hrs/day x 1 ton/2,000 lbs.

Plasma cutting emission factors are from the American Welding Society study published in Sweden (March 1994).

Welding and other flame cutting emission factors are from an internal training session document.

See AP-42, Chapter 12.19 for additional emission factors for welding.